



MenuControl)

Menu Code Reference

Dacons

© 2012 Dacons LLP. All rights reserved.

This tutorial assumes that you have elementary knowledge of FileMaker Pro and you know how to use plug-ins and external functions of this database platform.

This manual, as well as the software described in it, is furnished under a license and may not be copied, photocopied, reproduced, translated, or converted to any electronic or machine-readable form in whole or in part without prior written approval of Dacons LLP. Dacons assumes no responsibility or liability for any errors or inaccuracies that may appear in this manual.

Please send feedback to info@dacons.net

Website: <http://www.dacons.net>

This version of the manual was updated on December 26, 2012

CONTENTS

INTRODUCTION

About This Document	4
---------------------------	---

CHAPTER 1

Menu Code Tags	5
Menu Type Tag	6
Application Menu Tag	6
Script Item	6
Mac Quit Item	6
Menu Item Tag	7
FileMaker Item Tag	7
Cascading Sub Menu	7
Item String Tag	7
Menu Separator	7
Custom Keyboard Shortcut	7
Item Checkmark	8
Disable Menu Item	8
Platform Tags	8

CHAPTER 2

FileMaker Menu Constants	9
--------------------------------	---

INTRODUCTION

About This Document

This document explains the syntax of the menu code generated by MenuComposer 3. Thus, it targets advanced and professional MenuControl developers.

The menu code describes the structure of main, context and pop-up menus. It is passed to the MenuControl FileMaker plug-in as a parameter of functions that set menus.

You can use the MenuComposer to generate the menu code automatically. However, if you want to add or change specific menu items of a custom menu that has been installed before you need to pass the menu code for the item to be updated to the plug-in. Also, as an advanced FileMaker developer you may want change or create menu codes manually to save time.

CHAPTER 1

Menu Code Tags

The following is an example of a complete menu code as it could be used by the MenuControl plug-in to install a menu. You find bold capital letters in the left column of the listing starting with **A**. These letters indicate the description for certain menu code tags which you find further down in this section. The bold letters are not part of the actual menu code.

```
A  FM_MENUBAR ( )
    {
B      FM_APPMENU ( "My Solution" )
        {
C          FM_MENUSCRIPTITEM ( "About My Solution...", "About Script" )
D          FM_MACQUITITEM ( "Quit My Solution", "Close Script" )
E          FM_MENU ( FM_MENU_FILE )
F          FM_MENUITEM ( FM_OPEN )
G          FM_MENU ( "Go to Record" )
H          FM_MENUSCRIPTITEM ( "Smith", "Go to Record", String:"3423" )
I          FM_MENUITEM ( FM_CLOSE )
J          FM_MENUITEMSEPARATOR ( )
K          FM_MENUITEM ( FM_PRINT_SETUP )
L          FM_MENUSCRIPTITEM ( "Print...", "Print Script", CTRL + "P" )
        }
    }
    FM_MENU ( "Reports" )
    {
        FM_MENUSCRIPTITEM ( "Annual Report", "Show Annual Report", Check-On )
        FM_MENUSCRIPTITEM ( "Monthly Report", "Show Monthly Report", Disabled )
    }
    FM_MENU ( "Help" )
```

```

        {
            FM_MENUSCRIPTITEM ( "Help...", "Help Script" )
        }
    #IF_WIN
        FM_MENUSCRIPTITEM ( "About My Solution...", "About Script" )
    #END_IF
}

```

A Menu Type Tag

The first tag in the menu code indicates if the menu is a main menu (FM_MENUBAR), a context menu (FM_CONTEXTMENU) or a pop-up menu (FM_POPUPMENU). In main menus, script items and FileMaker menu items can not be located on the first level of the menu. All items of a menu have are located between the opening “{” and the closing “}” of the menu code.

B Application Menu Tag

The tag FM_APPMENU represents the application menu under Mac OS X and the Apple menu under Mac Classic. Menu items which are added between the opening “{” and the closing “}” will be shown in the application menu under Mac OS X. Under Mac Classic they will be shown in the Apple Menu when the application is in front. All items listed in the FM_APPMENU section of the menu code are ignored if the menu is set on Windows systems.

C Script Item

Menu items which trigger FileMaker scripts are represented by the tag FM_MENUSCRIPTITEM. This tag can have several options. Two are mandatory: The caption of the menu item is listed first in quotation marks (In the example it is “About My Solution...”). This is the name of the menu item which will appear in the menu. The second option is the name of the script which will be triggered when the menu item is selected by the user. The script name is enclosed in quotation marks, too. Note that the caption of the menu item can be different from the name of the script this item triggers.

D Mac Quit Item and Mac Preferences Item

The tag FM_MACQUITITEM is supported by Mac OS X only. The Quit menu item which is shown in the application menu of FileMaker and FileMaker runtime programs can not be removed by MenuControl. However, you can attach your own close script to this item by using the FM_MACQUITITEM tag. In addition, the tag FM_MACPREFERENCES which is not mentioned in the example above is also supported by Mac OS X only. It enables you to attach a custom script to the *Preferences* item of the FileMaker application shown under Mac OS X.

E Menu Item Tag

Main menu items are defined by the tag `FM_MENU`. The value `FM_MENU_FILE` shown in the example is used to tell the plug-in the local caption of the menu *File* is to be used according to the current FileMaker interface language. Alternatively, a fixed caption in quotation marks (“File”) could be used. In such a case the same caption would be used for all FileMaker languages.

F FileMaker Item Tag

The `FM_MENUITEM` tag represents default FileMaker menu items. It has two values. The first one is the optional fixed caption of the menu item as it will appear in the menu the user sees (text value enclosed in quotation marks followed by a comma). In the example this first value is omitted. This will have the effect that MenuControl shows the local caption of the FileMaker item defined by the second value according to the current FileMaker interface language. The second value is a FileMaker menu constant that tells MenuControl which FileMaker menu command will be triggered by the menu item. In the example this is `FM_OPEN` which represents the *File > Open* command of the default FileMaker menu. Alternatively, the tag `FM_MENUITEM` (“Open A File”, `FM_OPEN`) could be used in the example. This would result in MenuControl showing the fixed caption *Open A File* for this item regardless of the current FileMaker interface language.

For a complete list of supported FM menu constants review the section ***FileMaker Menu Constants***.

G Cascading Sub Menu

To add a cascading sub menu to an existing menu item the tag `FM_MENU` is used within the parentheses, “{” and “}”, of the parent menu item. There can be several levels of cascading menus.

H Item String Tag

Using the String tag invisible information can be saved with a script item or FileMaker item. Use this tag if additional information is required when the menu item is clicked by the user. In this example the caption of the menu item represents a record called *Smith*. To go to this record the script *Go to Record* which is triggered when the menu item *Smith* is clicked needs to know the record number. Therefore, the script calls the function *Cont-GetItemString*. The value it retrieves will be “3423” which is the record number of the record *Smith*.

I Menu Separator

The tag `FM_MENUITEMSEPARATOR` is used to show a separator in a menu. Use menu separators to visually group menu items.

J Custom Keyboard Shortcut

Script items and FileMaker menu items can have custom keyboard shortcuts. Indicating a shortcut is optional when specifying the settings of a `FM_MENUSCRIPTITEM`. `CTRL` represents the Ctrl-key on Windows PC keyboards. On Mac, this tag represents the Command-key (Note: not the Ctrl-

key!). In addition to the *CTRL* modifier, the modifier *ALT* is supported. It represents the Alt-key on Windows PC keyboards and the Option-key on Mac.

K Item Checkmark

Script items can have checkmarks. To show a checkmark the optional parameter *Check-On* is added to the FM_MENUSCRIPTITEM tag. This tag is not supported for FileMaker menu items.

L Disable Menu Item

Menu items can be disabled. To achieve this, the optional parameter *Disabled* id added to the FM_MENUSCRIPTITEM tag.

M Platform Tags

When developing a cross-platform solution which will be used on Windows and Mac systems you may want to show certain menu items only on specific platforms. By using platform tags you do not have to manage different menu codes for different platforms just because one or two items in the menu are different a Windows or a Mac system. You can specify the following platform tags:

#IF_WIN	: The menu item will be shown on Windows only
#IF_MAC	: The menu item will be shown on Mac OS X and Mac Classic
#IF_MACCARBON	: The menu item will be shown on Mac OS X only
#IF_MACCLASSIC	: The menu item will be shown on Mac Classic only

CHAPTER 2

FileMaker Menu Constants

The tag `FM_MENUITEM` in the menu code represents a default FileMaker menu item. The following table lists all FileMaker menu constants supported by MenuControl and their availability in different FileMaker versions and modes. If a FileMaker menu item is not available in a certain FileMaker version or mode it will be disabled automatically by the plug-in when it is shown in a menu.

Please note:

- Some menu items have been renamed in FileMaker 7 in comparison to earlier versions. The Menu Item column lists the latest FileMaker 7 name.
- Some items were available on Windows *or* Mac OS *only* before FileMaker 7. Since FileMaker 7 they are available on both platforms.
Examples:
`FM_WINDOW_CASCADE` and `FM_HIDE_WINDOW`. In such cases the table indicates that the menu item is supported under both Windows and Mac OS for all FileMaker versions it has ever been supported on.

The table starts on the next page.

Menu Item	Constant	OS		FileMaker Version				Platform			Mode		
		M	W	5.0	5.5	6.0	7/8	Pro	Dev	Run	B	F	P
File (Menu)	FM_MENU_FILE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
New Database	FM_NEW_DATABASE	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓
Open	FM_OPEN	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Open Remote	FM_OPEN_REMOTE	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓
Close	FM_CLOSE	✓	✓	✓	✓	✓	✓	✓	✓	✓			
Define Fields	FM_DEFINE_FIELDS	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓
Define Value Lists	FM_DEFINE_VALUE_LISTS	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓
Define Relationships	FM_DEFINE_RELATIONSHIPS	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓
Database Design Report	FM_DATABASE_DESIGN_REPORT	✓	✓			✓	✓	✓	✓		✓	✓	✓
Developer Utilities	FM_DEVELOPER_UTILITIES	✓	✓				✓		✓		✓	✓	✓
Passwords	FM_PASSWORDS	✓	✓	✓	✓	✓		✓	✓		✓	✓	✓
Groups	FM_GROUPS	✓	✓	✓	✓	✓		✓	✓		✓	✓	✓
Overview	FM_OVERVIEW	✓	✓	✓	✓	✓		✓	✓		✓	✓	✓
Sharing	FM_SHARING	✓	✓	✓	✓	✓		✓	✓		✓	✓	✓
Network Sharing	FM_NETWORK_SHARING	✓	✓				✓	✓	✓		✓	✓	✓
Web Sharing	FM_WEB_SHARING	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓
ODBC JDBC Sharing	FM_ODBC_JDBC_SHARING		✓				✓	✓	✓		✓	✓	✓
Define Database	FM_DEFINE_DATABASE	✓	✓				✓	✓	✓		✓	✓	✓
File Reference	FM_FILE_REFERENCES	✓	✓				✓	✓	✓		✓	✓	✓
Accounts & Privileges	FM_ACCOUNTS_PRIVILEGES	✓	✓				✓	✓	✓		✓	✓	✓
Change Password	FM_CHANGE_PASSWORD	✓	✓				✓	✓	✓		✓	✓	✓
Print Setup	FM_PRINT_SETUP	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Print	FM_PRINT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Import File	FM_IMPORT_FILE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Import Folder	FM_IMPORT_FOLDER	✓	✓			✓	✓	✓	✓	✓	✓	✓	✓
XML Data Source	FM_IMPORT_XML	✓	✓			✓	✓	✓	✓	✓	✓	✓	✓
ODBC Data Source	FM_IMPORT_ODBC	✓	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓
Digital Camera	FM_IMPORT_CAMERA	✓	✓			✓	✓	✓	✓	✓	✓	✓	✓
Export Records	FM_EXPORT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓
Save a Copy As	FM_SAVE_COPY	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Recover	FM_RECOVER	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
File Maintenance	FM_FILE_MAINTENANCE	✓	✓				✓	✓	✓	✓	✓	✓	✓
Open Recent	FM_RECENT_FILES	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓
Quit/Exit	FM_QUIT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Open Recent (Sub Menu)	FM_MENU_OPEN_RECENT	✓	✓				✓	✓	✓	✓	✓	✓	✓
Define (Sub Menu)	FM_MENU_DEFINE	✓	✓				✓	✓	✓	✓	✓	✓	✓
Access Privileges (Sub Menu)	FM_MENU_ACCESS_PRIVILEGES	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓
Import Records (Sub Menu)	FM_MENU_IMPORT_RECORDS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Edit (Menu)	FM_MENU_EDIT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Undo/Redo	FM_UNDO	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Cut	FM_CUT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Copy	FM_COPY	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Paste	FM_PASTE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Paste Special	FM_PASTE_SPECIAL		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Clear	FM_CLEAR	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Select All	FM_SELECT_ALL	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Find & Replace	FM_FIND_REPLACE	✓	✓			✓	✓	✓	✓	✓	✓	✓	
Find Again	FM_FIND_AGAIN	✓	✓			✓	✓	✓	✓	✓	✓	✓	
Replace & Find Again	FM_REPLACE_FIND_AGAIN	✓	✓			✓	✓	✓	✓	✓	✓	✓	
Find Selected	FM_FIND_SELECTED	✓	✓			✓	✓	✓	✓	✓	✓	✓	
Check Selection	FM_SPELLING_CHECK_SELECTION	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Check Record	FM_SPELLING_CHECK_RECORD	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
Check All	FM_SPELLING_CHECK_ALL	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
Correct Word	FM_SPELLING_CORRECT_WORD	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
Select Dictionaries	FM_SPELLING_SELECT_DICTIONARIES	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
Edit User Dictionary	FM_SPELLING_EDIT_USER_DICTIONARY	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
Links	FM_OBJECT_LINKS		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Show Objects	FM_SHOW_OBJECTS		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Convert	FM_CONVERT_OBJECTS		✓	✓	✓	✓	✓	✓	✓	✓	✓		
Preferences	FM_APP_PREFERENCES	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
File Options	FM_FILE_PREFERENCES	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Export Field Contents	FM_EXPORT_FIELD_CONTENTS	✓	✓				✓	✓	✓	✓	✓	✓	
Find/Replace (Sub Menu)	FM_MENU_FIND_REPLACE	✓	✓			✓	✓	✓	✓	✓	✓	✓	✓
Spelling (Sub Menu)	FM_MENU_SPELLING	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Object (Sub Menu)	FM_MENU_OBJECT		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Sharing (Sub Menu)	FM_MENU_SHARING	✓	✓				✓	✓	✓	✓	✓	✓	✓

Menu Item	Constant	OS		FileMaker Version				Platform			Mode		
		M	W	5.0	5.5	6.0	7/8	Pro	Dev	Run	B	F	P
Preferences (Sub Menu)	FM_MENU_PREFERENCES	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
View (Menu)	FM_MENU_VIEW	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Browse Mode	FM_BROWSE_MODE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Find Mode	FM_FIND_MODE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Layout Mode	FM_LAYOUT_MODE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Preview Mode	FM_PREVIEW_MODE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Form View	FM_FORM_VIEW	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
List View	FM_LIST_VIEW	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Table View	FM_TABLE_VIEW	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Standard (Toolbar)	FM_TOOLBARS_STANDARD	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Test Formatting (Toolbar)	FM_TOOLBARS_TEXT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Status Bar	FM_STATUS_BAR	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Status Area	FM_STATUS_AREA	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Text Ruler	FM_TEXT_RULER	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Zoom In	FM_ZOOM_IN	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Zoom Out	FM_ZOOM_OUT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Toolbars (Sub Menu)	FM_MENU_TOOLBARS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Insert (Menu)	FM_MENU_INSERT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Object	FM_INSERT_OBJECT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Picture	FM_INSERT_PICTURE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
QuickTime	FM_INSERT_QUICKTIME	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Sounds	FM_INSERT_SOUND	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
File	FM_INSERT_FILE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Current Date	FM_INSERT_CURRENT_DATE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Current Time	FM_INSERT_CURRENT_TIME	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Current User Name	FM_INSERT_CURRENT_USER_NAME	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
From Index	FM_INSERT_FROM_INDEX	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
From Last Visited Record	FM_INSERT_FROM_LAST_RECORD	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Format (Menu)	FM_MENU_FORMAT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Font	FM_TEXT_FONTS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Size	FM_TEXT_SIZE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Style	FM_TEXT_STYLE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Align Text	FM_TEXT_ALIGN	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Line Spacing	FM_TEXT_LINE_SPACING	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Line Color	FM_TEXT_COLOR	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Text	FM_TEXT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Use System Formats	FM_USE_SYSTEM_FORMATS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Record (Menu)	FM_MENU_RECORDS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
New Record	FM_NEW_RECORD	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Duplicate Record	FM_DUPLICATE_RECORD	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Delete All Records	FM_DELETE_ALL_RECORDS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Modify Last Find	FM_MODIFY_LAST_FIND	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Show All Records	FM_SHOW_ALL_RECORDS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Show Omitted Only	FM_SHOW_OMITTED_ONLY	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Omit Record	FM_OMIT_RECORD	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Omit Multiple Records	FM_OMIT_MULTIPLE_RECORDS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Sort Records	FM_SORT_RECORDS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Unsort Records	FM_UNSORT_RECORDS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Replace Field Contents	FM_REPLACE_CONTENTS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Relookup Field Contents	FM_RELOOKUP_CONTENTS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Revert Record	FM_REVERT_RECORD	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Request (Menu)	FM_MENU_REQUESTS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
New Request	FM_NEW_REQUEST	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Duplicate Request	FM_DUPLICATE_REQUEST	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Delete Request	FM_DELETE_REQUEST	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Perform Find	FM_PERFORM_FIND	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Constrain Found Set	FM_CONSTRAIN_FOUND_SET	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Extend Found Set	FM_EXTEND_FOUND_SET	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Revert Request	FM_REVERT_REQUEST	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

Menu Item	Constant	OS		FileMaker Version				Platform			Mode		
		M	W	5.0	5.5	6.0	7/8	Pro	Dev	Run	B	F	P
Scripts (Menu)	FM_MENU_SCRIPTS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
ScriptMaker	FM_SCRIPTMAKER	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓
Debug Scripts	FM_DEBUG_SCRIPTS	✓	✓	✓	✓	✓	✓		✓		✓	✓	✓
List of scripts	FM_SCRIPTS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Window (Menu)	FM_MENU_WINDOW	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Tile Horizontally	FM_WINDOW_TILE_HORIZONTALLY	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Tile Vertically	FM_WINDOW_TILE_VERTICALLY	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Cascade Windows	FM_WINDOW_CASCADE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Arrange Icons	FM_WINDOW_ARRANGE_ICONS		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
List of open windows	FM_OPEN_WINDOWS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Bring All to Front	FM_WINDOW_ALL_TO_FRONT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
New Window	FM_NEW_WINDOW	✓	✓				✓	✓	✓	✓	✓	✓	✓
List of hidden windows	FM_HIDDEN_WINDOW	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Hide Window	FM_HIDE_WINDOW	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Minimize Window	FM_MINIMIZE_WINDOW	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Show Window (Sub Menu)	FM_MENU_SHOW_WINDOW	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Help (Menu)	FM_MENU_HELP	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
FileMaker Help	FM_HELP	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Keyboard Commands	FM_HELP_KEYBOARD	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Contents and Indexes	FM_HELP_CONTENTS_INDEXES	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
What's This?	FM_HELP_WHATS_THIS		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
FileMaker on the Web	FM_WEBSITE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Send Feedback to FileMaker	FM_SEND_FEEDBACK	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Register Now	FM_REGISTER_NOW	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
About FileMaker	FM_ABOUT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓